

# xPAR™ -38

Fixed Wattage, Ultra-Light  
NON-DIMMABLE



xPAR-38



## PRODUCT SUMMARY

- Fixed Wattage
- Non-Dimmable
- Multiple Color Temperatures Available
- Custom Optics
- High Color Rendering
- CrimpFin™ Heat Sink Technology
- 50,000 hour life, 5 year warranty
- Halogen PAR form factor (ANSI compliant)
- No UV or IR radiation
- Voltage: 120v
- 0.9 Power Factor
- Socket Type: Medium Screw Base
- Environment: Dry
- Length: 5 in, 127 mm
- Diameter: 4.8 in, 122mm
- Weight: 8.32 ounces, 236 g
- Operating Temperature -20° C + 45° C

120~

220~



2700K

3000K



The high power xPAR38 lamps from MSi are 14W fixed, outperforming a 75-watt halogen PAR lamp. This amazing lamp brings together the latest innovation and experience from MSi's multiple engineering disciplines to deliver the complete solution for retail, hospitality, furniture, museum and commercial applications.



Catalog #	Power	CCT (K)	CRI	Beam Angle	Lumens	CBCP
xPAR38271514T3N	14W	2700	82	15°	900	9,700
xPAR38272514T3N				25°		3,800
xPAR38301514T3N	14W	3000	82	15°	1000	10,750
xPAR38302514T3N				25°		4,250
xPAR38401514T3N	14W	4000	82	15°	1100	11,850
xPAR38402514T3N				25°		4,630




# xPAR™-38


## CANDELA DISTRIBUTION

15°

3000K



## BEAM DISTRIBUTION





## 0° AIMING FOOTCANDLES

Distance To Floor	Beam Diameter (50% CBCP)	Footcandles On Floor
5'	1.3'	430
10'	2.6'	108
15'	3.9'	48
20'	5.3'	27

25°

3000K



Distance To Floor	Beam Diameter (50% CBCP)	Footcandles On Floor
5'	2.2'	170
10'	4.4'	43
15'	6.7'	19
20'	8.9'	11

**CAUTION:** Risk of electric shock. Do not open - no user serviceable parts inside. Use in dry locations only. Turn power off before inspection, installation, or removal. Not intended for use with emergency exit fixtures or emergency exit lights. Not for use where exposed to the weather. Not for use with totally enclosed fixtures or fixture that inhibit air flow.

**WARRANTY** - This product is covered by a 5 year limited warranty under normal operating conditions based on 12 hours of usage per day. For details please visit [www.msissl.com/warranty.html](http://www.msissl.com/warranty.html)